



A HANDE HANDER BOOKEN BOOKEN DE STEEN DE SANDER BOOK OF DIE ZALON VIEWEN DE STEEN EE

### Flexible Expansion

Up to 16 units in parallel, 2.56kWh--40.96kWh capacity



# 1.3C Discharge

Simultaneously supplying power to multiple loads, no need to worry about power outages



# Easy Installation

30% less volume, high space utilization



### All-round Safety

Short-circuit lockout, surge-resistant, safe and reliable



### **Battery Equalization**

Support extreme mixing of modules at 0% and 100% charge



#### **Smart Management**

Real-time system monitoring, remote control, OTA updates

Model	DL2.5
Cell Technology	LiFePO <sub>4</sub>
Battery Module Capacity	2.56 kWh
Battery Module Voltage	25.6V
Battery Module Capacity	100 Ah
Battery Module Charge Voltage	28.5V
Recommended Charge/Discharge Current	50A
Max. Charge Current	75A
Max. Discharge Current	130A
Depth of Discharge (DOD)	90%
Cycle Life *	≥6000
Dimension(W/D/H, mm)	481/221/133
Communication	CAN/RS485
WIFI Module	Optional
IP Grade	IP2O
Weight	23kg
Charging Temp. Range	0°C~+55°C
Discharging Temp. Range	-20°C~+55°C
Compatible Inverters	Steca/Sorotec/Must/Victron/Growatt
Certification	UN38.3/CE-EMC/IEC62619/ECE R10/GOST-R

<sup>\*</sup> Test conditions: 0.2C Charging & Discharging. @25°C, 90% DOD

